

SAFETY DATA SHEET

Dr Beckmann Stain Slayer

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Dr Beckmann Stain Slayer
 SUPPLIER ACDOCO Ltd
 Kelly Street
 Blackburn
 Lancs BB2 4PJ
 0845 017 8000
 0845 017 8001

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	15-30%	F+;R12
Combination of chloromethyl-/methylisothiazolone			less than 5%	R43.
Orange Terpenes		8028-48-6	more than 30%	Xn;R65. R10.
POTASSIUM HYDROXIDE	215-181-3	1310-58-3	less than 5%	C;R35 Xn;R22

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Extremely flammable. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R38. F+;R12. R52/53.

4 FIRST-AID MEASURES

INHALATION

Move into fresh air and keep at rest. In the event of symptoms see a physician.

INGESTION

DO NOT induce vomiting. Get medical attention immediately. Immediately rinse mouth and drink plenty of water (200-300 ml).

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Immediately rinse with water for several minutes. Consult a physician for specific advice.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Small fires: Water spray, carbon dioxide, dry powder or polar resistant foam. Larger fires: Alcohol resistant foam. Water spray.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Do not smoke, use naked flames or other sources of ignition. Wear protective clothing as described in Section 8 of this safety data sheet.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Eliminate all sources of ignition. Do not smoke while using.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

STORAGE CLASS

Flammable compressed gas storage.

Dr Beckmann Stain Slayer

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
POTASSIUM HYDROXIDE	WEL				2 mg/m3
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3

HAND PROTECTION

PVC gloves are recommended.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid				
COLOUR	Colourless				
ODOUR	Orangey				
SOLUBILITY	Emulsifiable in water.				
BOILING POINT (°C)	175	RELATIVE DENSITY	0.84 20C		
FLASH POINT (°C)	50-58 for product				

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Extremes of temperature

MATERIALS TO AVOID

Strong acids. Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

SKIN CONTACT

Irritating to skin.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION

MOBILITY

The product has not been tested.

BIOACCUMULATION

No data available on bioaccumulation.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Do not pierce or burn, even empty containers.

DISPOSAL METHODS

Product and empty containers should be disposed of in accordance with national regulations.

14 TRANSPORT INFORMATION

