

## SAFETY DATA SHEET

### Stain Devils Grease, Lubricant & Paint

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME                      Stain Devils Grease, Lubricant & Paint

SUPPLIER                              ACDOCO Ltd  
Mallison Street  
Bolton  
Lancashire BL1 8PP  
Tel 01204 600500  
Fax 01204 600501

#### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	less than 5%	R10
3,6,9,12-tetraoxatetracosan-1-ol		5274-68-0	less than 5%	Xi;R41. N;R50.
ETHANOL	200-578-6	64-17-5	15-30%	F;R11
Fatty alcohol ethoxylate		24938-91-8	5-15%	Xn;R22. Xi;R41.
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	265-150-3	64742-48-9	more than 30%	Xn;R65. R66.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	265-151-9	64742-49-0	15-30%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
Non-ionic surfactant		69011-36-5	5-15%	Xi;R41.

The Full Text for all R-Phrases are Displayed in Section 16

#### 3 HAZARDS IDENTIFICATION

Highly flammable. Risk of serious damage to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

CLASSIFICATION                      Xn;R65. Xi;R41. F;R11. R52/53, R66, R67.

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Remove contaminated soaked clothing immediately.

##### INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

##### INGESTION

Wash out mouth with water. Drink plenty of water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs.

##### SKIN CONTACT

Rinse with water. Contact physician if discomfort continues.

##### EYE CONTACT

Rinse with water for 15 minutes. Obtain medical attention and bring these instructions.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Water spray. Carbon dioxide (CO2). Powder.

##### SPECIAL FIRE FIGHTING PROCEDURES

Use water to keep fire exposed containers cool and disperse vapours. Avoid breathing fire vapours. Keep run-off water out of sewers and water sources. Dike for water control.

### Stain Devils Grease, Lubricant & Paint

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Vapours are heavier than air and may spread near ground to sources of ignition. Vapours may form explosive mixture with air at room temperature.

**SPECIFIC HAZARDS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2). In case of fire, toxic gases may be formed.

**PROTECTIVE MEASURES IN FIRE**

Wear protective clothing. Wear breathing apparatus

**6 ACCIDENTAL RELEASE MEASURES**

**PERSONAL PRECAUTIONS**

Ensure adequate ventilation. Wear appropriate protective clothing ---- See section 8 Use breathing apparatus if exposed to vapours.

**ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, surface water or ground water. Avoid discharge onto the ground.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**7 HANDLING AND STORAGE**

**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Do not smoke while using. Static electricity and formation of sparks must be prevented.

**USAGE DESCRIPTION**

Use solvent resistant equipment.

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry, cool and well-ventilated place. Provide solvent-resistant and impermeable floor. Do not store together with explosive or flammable materials and oxidising agents.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(Sk)
ETHANOL	WEL	1000 ppm	1920 mg/m3		
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	WEL				

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided.

**HAND PROTECTION**

Chemical resistant gloves required for prolonged or repeated contact.

**EYE PROTECTION**

If risk of splashing, wear safety goggles or face shield.

**OTHER PROTECTION**

PROTECTIVE CLOTHING.

**HYGIENE MEASURES**

Promptly remove any clothing that becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid
COLOUR	Colourless
ODOUR	Petroleum.
SOLUBILITY	Slightly soluble in water. Soluble in Organic solvents

**Stain Devils Grease, Lubricant & Paint**

RELATIVE DENSITY	0.8	FLASH POINT (°C)	<10
AUTO IGNITION TEMPERATURE (°C)	Not self igniting		

**10 STABILITY AND REACTIVITY**

CONDITIONS TO AVOID

Containers are liable to burst if temperature rises. Avoid contact with strong oxidisers.

HAZARDOUS DECOMPOSITION PRODUCTS

During fire, toxic gases (CO, CO2) are formed.

**11 TOXICOLOGICAL INFORMATION**

TOXIC DOSE 1 - LD 50	>5000 mg/kg (oral rat)
TOXIC DOSE 2 - LD 50	>3000 mg/kg (oral-rbt)
TOXIC CONC. - LC 50	>5 mg/l/4h (inh-rat)

TOXICOLOGICAL INFORMATION

Above data is for 64742-48-9 Naphtha (petroleum), hydrotreated heavy

SKIN CONTACT

Product has a defatting effect on skin. Prolonged and repeated contact may cause a dermatitic effect.

EYE CONTACT

Risk of serious damage to eyes.

**12 ECOLOGICAL INFORMATION**

ECOTOXICITY

No data on possible environmental effects have been found.

LC 50, 96 Hrs, FISH mg/l	<100
--------------------------	------

MOBILITY

The product has not been tested.

BIOACCUMULATION

The product has not been tested.

WATER HAZARD CLASSIFICATION

Hazardous for water

**13 DISPOSAL CONSIDERATIONS**

DISPOSAL METHODS

Product and empty containers should be disposed of in accordance with national regulations.

**14 TRANSPORT INFORMATION**



UK ROAD CLASS	3	UK ROAD PACK GR.	II
PROPER SHIPPING NAME	FLAMMABLE LIQUID, N.O.S. (ETHANOL, NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)		
ROAD TRANSPORT NOTES	Limited quantity		
UN NO. ROAD	1993	ADR CLASS	Class 3: Flammable liquids.
ADR CLASS NO.	3		

### Stain Devils Grease, Lubricant & Paint

ADR PACK GROUP	II	HAZARD No. (ADR)	33
ADR LABEL NO.	3	HAZCHEM CODE	3YE
CEFIC TEC(R) NO.	30GF1-I+II, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1993
IMDG CLASS	3	IMDG PACK GR.	II
EMS	F-E, S-E	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1993
AIR CLASS	3	AIR PACK GR.	II

#### 15 REGULATORY INFORMATION

LABELLING



Harmful



Highly Flammable

CONTAINS

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY  
 NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

RISK PHRASES

R11	Highly flammable.
R41	Risk of serious damage to eyes.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children
S16	Keep away from sources of ignition - No smoking.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29/56	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
S39	Wear eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.

#### 16 OTHER INFORMATION

REVISION DATE 1/06/2007

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R22	Harmful if swallowed.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R50	Very toxic to aquatic organisms.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.